Farmax Spaders

www.spaders.com.au

Operational working suggestions for the **best** outcome

- Know your soil profile
- Pre ripping improves the mixing
- Level the big furrows after delving
- Spade at 20 50 degree angle across the ripping / delving
- Deeper spading needs slower speed





Farmax Spaders

Groocock Soil Improvement Pty Ltd

Groocock Soil Improvement

PO Box 484 Bordertown SA 5268

Phone/Fax: 08 8754 6025 Mobile: 0427 546 025

Email: grooks@internode.on.net
Website: www.spaders.com.au



The Farmax spader is a digging machine which mixes soil thoroughly to a depth of 200 – 400mm incorporating clay, lime, stubble, green manure, fertilizer and / or trace elements.

www.spaders.com.au



With the introduction of the Farmax 300 and 400 a new generation of digging machines is created.



Bott on spades allow easier replacement and the bolts give some shearpin protection.

Standard with PTO slip clutch and finger tyne roller.

Depending on the soil type or desired result, the Farmax 300 and 400 can be fitted with a rotovator cage roller or flat roller to produce a perfect seed bed.

Technical data

Working width	3.00m	4.00m
Number spades	24	30
Weight	2940kg	3500kg
Power	160 – 200 Hp	200 – 300 Hp
	119 – 149 kw	149 – 224 kw
Capacity	Up to 1.8 ha/h	Up to 2.4 ha/h
Working depth	200 - 400mm	200 - 400mm
PTO rpm	1000 rpm	1000 rpm
Finger tyne roller	400mm	400mm





Green Manuring with the Farmax Spader



Groocock Soil Improvement Pty Ltd

PO Box 484 Bordertown SA 5268

Phone/Fax: 08 8754 6025 Mobile: 0427 546 025

Email: grooks@internode.on.net Website: www.spaders.com.au